

Solar Performance Neutral Appearance

Neutrals



Benefits

- Great heat rejection helps provide energy savings and improved comfort
- Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading
- Helps reduce glare and eye discomfort
- Soft hues make this film very attractive in both residential and commercial settings
- Comprehensive warranty from 3M

Energy Savings ★ ★

Heat Rejection ★ ★

Glare Reduction ★ ★

Visible Reflection ★ ★

In comparison to other 3M™ Sun Control Window Films

Best ★★★★★ Better ★★★ Good ★★ Fair ★

Valued Associations & Alliances



Neutrals Case Study

Century Plaza Tower, Los Angeles, California

Climate Zone 3

11,000 windows installed with Neutral 35

Payback period — less than 8 months

Customer Issues:

- Energy costs
- Temperature imbalances



Product Performance & Technical Data

Glass Type (All 1/4")	Film Type	Visible Light			Total Solar Energy Rejected	Solar Heat Gain Coefficient	U Value	Solar Heat Reduction	UV Light Rejected	Glare Reduction	Visible Light to Solar Heat Gain Ratio
		Reflected (Interior)	Reflected (Exterior)	Transmitted							
 Clear	Neutral 20	19%	21%	15%	62%	0.38	0.99	53%	99%	83%	0.4
	Neutral 35	18%	20%	36%	56%	0.44	0.99	46%	99%	60%	0.8
	Neutral 50	11%	12%	52%	44%	0.56	1.03	31%	98%	41%	0.9
	Neutral 70	8%	9%	69%	32%	0.68	1.03	17%	98%	22%	1.0
 Tinted	Neutral 20	19%	10%	9%	68%	0.32	0.99	49%	99%	83%	0.3
	Neutral 35	18%	10%	21%	61%	0.39	0.99	38%	99%	60%	0.5
	Neutral 50	10%	7%	31%	53%	0.47	1.03	25%	99%	41%	0.7
	Neutral 70	7%	6%	42%	45%	0.55	1.03	13%	99%	22%	0.8
 Double Clear	Neutral 20	19%	25%	14%	54%	0.46	0.47	34%	99%	83%	0.3
	Neutral 35	19%	24%	32%	49%	0.51	0.46	27%	99%	60%	0.6
	Neutral 50	13%	18%	46%	41%	0.59	0.48	16%	99%	41%	0.8
	Neutral 70	12%	16%	62%	36%	0.64	0.48	8%	99%	22%	1.0
 Double Tinted	Neutral 20	19%	12%	8%	64%	0.36	0.47	30%	99%	83%	0.2
	Neutral 35	19%	12%	19%	61%	0.39	0.46	23%	99%	60%	0.5
	Neutral 50	13%	10%	28%	57%	0.44	0.48	14%	99%	41%	0.6
	Neutral 70	11%	9%	37%	53%	0.47	0.48	7%	99%	22%	0.8

LEED Certification

Window films may be used towards the following LEED credits:

- SS-8
- MR 1.1-1.2
- EQ-7.1
- EQ-8.1-8.2
- EA-1
- MR 5.1-5.2
- EQ-7.2
- ID

Warranty, Limited Remedy and Disclaimer: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Contáctanos

www.tecip.com.pe



Escribenos o llámanos

986-650-380 | 981-175-599 | 942-780-265



@tecip.com.pe

